

Apply Tags to Inventory Records

If tags have been enabled, then every single inventory record will be associated with those tags. However, items do not need to have tags specified in the order data. If an item does have a tag name provided in the order, then an associated value must be included as well.

For example, if your configuration has the tags OrderType and Channel and you only care about a certain item's OrderType, then specify the OrderType tag and its value. Do not include the Channel tag and it will be set to the default. If neither of these tags mattered for the product, then would exclude them both from the item data.

Set Tags via API

An example of an [Inventory Refresh](#) call that sets inventory data with discrete tag values:

```
{
  "locationCode": "examplelocation",
  "items": [
    {
      "upc": "AD1001",
      "quantity": 100,
      "tags": {
        "Channel": "Warehouse"
      }
    },
    {
      "upc": "AD1001",
      "quantity": 50,
      "tags": {
        "Channel": "Target"
      }
    }
  ]
}
```

Upload Tagged Inventory Files

The [inventory import process](#) also supports segmentation, so you can use this file upload to apply your tags instead of doing it via API. To do this, add the tag name as a column header after the default headers and insert the tag value into the column value. The example below shows a sample file with Channel and OrderType tag columns:

```
LOCATIONCODE,PARTNUMBER,UPC,SKU,QUANTITY,DELIVERY_DATE,Channel,OrderType
Spatula_LA_WH,SpatulaTestPartNumber,SpatulaTestUPC,SpatulaTestSKU,10,,,
Spatula_DAL_WH,SpatulaTestPartNumber3,SpatulaTestUPC3,SpatulaTestSKU3,30,,Amazon,Carrier Pigeon
```